



LZJ₂-2000

门窗铰链钻孔机 Hinge Drilling Machine

[性能特点]

- 用于铝门窗（外开窗、上悬窗等）的铰链安装孔、滑撑风撑孔、四连杆孔的高效钻孔加工。
- 一次装夹可同时加工两侧共十个孔，加工效率极高。
- 采用台湾高精度多轴钻包，关键旋转部位均采用精密进口轴承，确保加工精度及使用寿命。
- 脚踏开关控制动作，操作简便。

[Product Features]

- It used for drilling hinge installing hole, sliding support hole and four connecting rod hole of aluminum window and door profile (outward window and tilt Windows, etc).
- It can process on both sides of total 10 holes at one time, machining efficiency is very high.
- It used of high precision multi axis drilling package from Taiwan to ensure machining accuracy and service life.
- Foot switches control action, easy to operate.

技术参数 Technical Parameters

工作电压	Power supply	380V 50HZ
工作气压	Operation air pressure	0.6~0.8MPa
加工宽度	Process width	300~2000mm
钻孔直径	Drilling diameter	Φ1~Φ7
最小孔距	Min hole distance	22mm
最大孔距	Max hole distance	380mm
输出功率	Output power	3KW
主轴转速	Spindle speed	1400rpm
外形尺寸	Contour dimension	3100 × 1200 × 960(mm)
重量	Weight	750Kg